

	Record 5100	Horton 2000	Besam Uni-Slide
Standard Warranty (complete unit)	2 years	1 year	1 year
Standard Top Roller Track Warranty	Lifetime	1 year	1 year
Standard Top Roller Warranty	3 years	1 year	1 year
Rollers per panel*	4	4	2
Operating Temperature Range	negative 40 to 140 Fahrenheit	negative 30 to 130	negative 35 to 122 Fahrenheit
Maximum Door Panel Weight, bi-part	300 lbs	250 lbs	220 lbs
Header Size*	4-1/2" x 7"	4" x 6"	7-5/8" x 6-5/8"
Break-out panel control*	Concealed Hydraulic Closer	Torsion Spring	Hydraulic Dampner (optional)
FBO, 1" glazing	SO & SX	SO & SX	SX only
Door Panel Construction*	Mortise Block	Mortise Block	Mortise Block
Diagnostics	Exposed via LCD	Horton Personell Only	Besam Personell Only
Life cycle counter	Exposed via LCD	NA	Besam Personell Only
Safety Adjustments	Software limits to ANSI 156.10	Relies on Service Tech to comply	Relies on Service Tech to comply
Weather Stripping	Extruded Channel in Door Panels	Extruded in Door Panels	Extruded Chanbel in Door Panels
Standard Safety Detection	2 infrared curtains, 2 beams	2 infared curtains, 2 beams	2 infared curtains
Uni-Directional Motion Detection	Standard	Standard	Standard
Bottom Guide Design*	Round Pin	Round Pin	Round Pin
Power Consumption, Peak Operation	100 Watts	300 Watts	250 Watts
Motor Size****	1/8 HP	1/8 HP	1/8 HP

***Rollers per panel**: 4 rollers per panel allows weight distribution for smooth, quiet operation, no binding

***Header Size**: 4-1/2" wide header sits flush with standard storefront framing

***Break-out Panel Control**: Hydraulic closer controls door panel in break-out mode and create soft 90 degree stopping point